

K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

HANSA FLEX

Savybės

Darbinis slėgis	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
Temperatūros diapazonas	-10 °C to +60 °C
6 bar ir 10 bar srautas	550 NI/min
6 bar ir 5 bar srautas	400 NI/min
Vožtuvo korpusas	Aliuminis
Spyruoklė	Special steel
Stūmoklis	Aluminium
Sandarinimo medžiaga	NBR



Nuoroda

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Daugiau duomenų pagal užklausimą.

Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

Prekė

Pavadinimas	Jungtis	Simbolis	Aktyvinimo įtaisas	Jungimo padėtys
K- 07 15 00 82	G 1/8	9	monostable	2
K- 07 15 00 83	G 1/8	10	bistabilus	2
K- 07 15 00 84	G 1/8	11	monostable	3*
K- 07 15 00 85	G 1/8	12	bistabilus	3*