

# K-WV 3/2 MANU PILZTAST NOT

3/2-way pilot valve, manually operated, with mushroom pushbutton and emergency latch, NC

**HANSA FLEX**

## Savybės

|                                |   |
|--------------------------------|---|
| <b>Darbinis slėgis</b>         | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| <b>Temperatūros diapazonas</b> | -10 °C to +60 °C  |
| <b>6 bar ir 10 bar srautas</b> | 550 NI/min  |
| <b>6 bar ir 5 bar srautas</b>  | 400 NI/min  |
| <b>Aktyvinimo įtaisas</b>      | Monostable  |
| <b>Vožtuvo korpusas</b>        | Aliuminis   |
| <b>Spyruoklė</b>               | Special steel   |
| <b>Stūmoklis</b>               | Aluminium   |
| <b>Sandarinio medžiaga</b>     | NBR   |



## Nuoroda

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Daugiau duomenų pagal užklausimą.

## Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

## Prekė

| Pavadinimas    | Jungtis | Simbolis | Aktyvinimo įtaisas |
|----------------|---------|----------|--------------------|
| K- 07 15 00 87 | G 1/8   | 14       | monostable         |