

# K-WV 3/2 MANU PILZTAST NOT

3/2-way pilot valve, manually operated, with mushroom pushbutton and emergency latch, NC

**HANSA FLEX**

## Savybės

<b>Darbinis slėgis</b>	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
<b>Temperatūros diapazonas</b>	-10 °C to +60 °C
<b>6 bar ir 10 bar srautas</b>	550 NI/min
<b>6 bar ir 5 bar srautas</b>	400 NI/min
<b>Aktyvinimo įtaisas</b>	Monostable
<b>Vožtuvo korpusas</b>	Aliuminis
<b>Spyruoklė</b>	Special steel
<b>Stūmoklis</b>	Aluminium
<b>Sandarinio medžiaga</b>	NBR



## Nuoroda

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Daugiau duomenų pagal užklausimą.

## Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

## Prekė

Pavadinimas	Jungtis	Simbolis	Aktyvinimo įtaisas
K- 07 15 00 87	G 1/8	14	monostable