

K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

HANSA FLEX

Savybės

Darbinis slėgis	0 - 35 bar
Medžiagos temperatūra	-20 °C to +100 °C
Korpusas	Brass
Apsauga ir sandarinimas	Industrial glue, mid hardened



Nuoroda

Couplings and distributors are also available separately
Daugiau duomenų pagal užklausimą.

Aprašas

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Papildoma informacija

Couplings and distributors are also available separately

Prekė

Pavadinimas	Jungtis	Mova	sudarytas iš skirstytuvų
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

priedai šiems gaminiams

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«