

K-VT 3 KUPPL 7,2 AG MS

Distributors with 3 quick disconnect couplings DN 7.2, brass, male

HANSA FLEX

Savybės

| | |
|-------------------------|-------------------------------|
| Darbinis slėgis | 0 - 35 bar |
| Medžiagos temperatūra | -20 °C to +100 °C |
| Korpusas | Brass |
| Apsauga ir sandarinimas | Industrial glue, mid hardened |



Nuoroda

Couplings and distributors are also available separately
Daugiau duomenų pagal užklausimą.

Aprašas

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Papildoma informacija

Couplings and distributors are also available separately

Prekė

| Pavadinimas | Jungtis | Mova | sudarytas iš skirstytuvų |
|----------------|------------|------------|--------------------------|
| K- 07 35 00 54 | G 1/4 male | K-07350025 | K-07404018 |
| K- 07 35 00 55 | G 3/8 male | K-07350025 | K-07404018 |
| K- 07 35 00 56 | G 1/2 male | K-07350026 | K-07404019 |