

# K-LP ALU O DUESE

Blow guns die-cast aluminium nickel-plated, without nozzle, Safety

**HANSA FLEX**

## Savybės

|                          |                  |
|--------------------------|------------------|
| Darbinis slėgis          | maks. 10 bar     |
| Darbinė temperatūra      | -10 °C to +50 °C |
| Purkštukai ir ilgintuvai | Thread M12x1.25  |



## Nuoroda

Daugiau duomenų pagal užklausimą.

## Aprašas

Standard type without nozzle! In combination with the safety nozzles described below, this blow gun meets a wide range of safety requirements. For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

## Prekė

| Pavadinimas    | Jungtis                                | Jungties sriegis |
|----------------|--|------------------|
| K- 07 10 00 07 | Stem, I.D. 6                           | G 1/4            |
| K- 07 10 00 10 | Stem, I.D. 9                           | G 1/4            |
| K- 07 10 00 14 | Stem, I.D. 13                          | G 1/4            |
| K- 07 10 00 18 | connection nipples for coupling NW 7,2 | G 1/4            |

## Priedai

|                              |  |
|------------------------------|--|
| K-ZUBEH LP ALU               | Accessories for standard blow guns (series 22)     |
| K-FEINSTRAHL DUE LAERMARME M | Low-noise fine-spray nozzles, M12x1.25 connection  |
| K-RUNDDUESE LAERMARME M      | Low-noise round nozzles, M12x1.25 connection       |
| K-FLACHDUESE LAERMARME M     | Low-noise flat nozzles, M12x1.25 connection        |
| K-STANDARD DUESE             | Standard nozzle (short version) with Ø 1.5 mm bore |
| K-DAEMPFER DUESE             | Silencer nozzle, M12x1.25 connection               |
| K-DUESE MIT SCHUTZSCHILD     | Nozzle with chip shield, M12x1.25 connection       |
| K-VERL DUESE                 | Extension nozzles                                  |
| K-DRUCKREGULIER DUESE        | Regulating nozzle, M12x1,25, Safety                |