K-RUNDDUESE LAERMARME

Low-noise round nozzles



Nuoroda

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

Aprašas

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

Prekė

Pavadinimas	Sriegis	Ilgis (mm)	Purkštukų Ø išorėje (mm)	Medžiaga	Diagrama
K- 07 10 09 56	G 3/8 male	55,0	11	Nickel-plated brass	3
K- 07 10 09 57	G 3/8 male	50,0	10	aliuminis	4
K- 07 10 09 58	G 1/4 male	41,0	13	aliuminis	5
K- 07 10 09 59	G 1/4 male	46,0	17	Die cast zinc	6
K- 07 10 11 14	G 1/4 male	40,0	17	Plastic (POM)	7
K- 07 10 11 15	G 1/4 male	35,0	11	aliuminis	8
K- 07 10 11 16	G 1/4 male	47,0	19	Die cast zinc	9
K- 07 10 11 17	G 1/4 male	55,0	19	Plastic (ABS)	10

Nepaisant kruopštaus patikrinimo, negalime atmesti klaidų tikimybės, todėl už esamus duomenis neatsakome.