

K-RUNDDUESE LAERMARME

Low-noise round nozzles

HANSA FLEX



Nuoroda

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

Aprašas

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

Prekė

| Pavadinimas | Sriegis | Ilgis (mm) | Purkštukų Ø išorėje (mm) | Medžiaga | Diagrama |
|----------------|------------|---------------|-----------------------------|---------------------|----------|
| K- 07 10 09 56 | G 3/8 male | 55,0 | 11 | Nickel-plated brass | 3 |
| K- 07 10 09 57 | G 3/8 male | 50,0 | 10 | aliuminis | 4 |
| K- 07 10 09 58 | G 1/4 male | 41,0 | 13 | aliuminis | 5 |
| K- 07 10 09 59 | G 1/4 male | 46,0 | 17 | Die cast zinc | 6 |
| K- 07 10 11 14 | G 1/4 male | 40,0 | 17 | Plastic (POM) | 7 |
| K- 07 10 11 15 | G 1/4 male | 35,0 | 11 | aliuminis | 8 |
| K- 07 10 11 16 | G 1/4 male | 47,0 | 19 | Die cast zinc | 9 |
| K- 07 10 11 17 | G 1/4 male | 55,0 | 19 | Plastic (ABS) | 10 |