



# K-VLST K AG-K IG MS NI

Extensions, short, conical male thread, parallel female thread - nickel-plated brass

**HANSA FLEX**

## Savybės

Darbinė temperatūra	Max. 150 °C
Slėgis	Max. 60 bar
Medžiaga	Žalvaris, nikeluotas



## Nuoroda

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Daugiau duomenų pagal užklausimą.

## Aprašas

Suitable for air, water, oil, steam, etc.

## Papildoma informacija

Further types and dimensions on request.

## Prekė

Pavadinimas	Sriegiai išorėje	Sriegiai viduje	L1 (mm)	L2 (mm)	SW (rakto dydis)
K- 07 40 38 91	R 1/8	G 1/8	20,0	8,0	14 mm
K- 07 40 38 92	R 1/8	G 1/4	22,5	8,0	17 mm
K- 07 40 38 98	R 1/8	G 3/8	22,5	8,0	22 mm
K- 07 40 38 93	R 1/4	G 1/4	25,0	11,0	17 mm
K- 07 40 38 94	R 1/4	G 3/8	28,5	11,0	22 mm
K- 07 40 38 95	R 1/4	G 1/2	29,0	11,0	24 mm
K- 07 40 38 96	R 3/8	G 3/8	28,5	11,5	22 mm
K- 07 40 38 97	R 3/8	G 1/2	32,0	11,5	24 mm
K- 07 40 38 99	R 1/2	G 1/2	34,0	14,0	24 mm
K- 07 40 39 00	R 1/2	G 3/4	35,0	14,0	32 mm