

# K-SPIR SCHL KUPPL SET LKM NW 7,6

Spiral hose and coupling kits, with safety couplings DN 7.6

**HANSA FLEX**

## Savybės

|                       |                  |
|-----------------------|------------------|
| Darbinis slėgis       | 10 bar           |
| Medžiagos temperatūra | -20 °C to +60 °C |



## Nuoroda

Daugiau duomenų pagal užklausimą.

## Aprašas

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Prekė

| Pavadinimas    | Žarnos matmuo  | Spiralės Ø<br>(mm) | Darbinis ilgis<br>(m) |
|----------------|----------------|--------------------|-----------------------|
| K- 07 10 07 65 | 10 mm x 6,5 mm | 52                 | 2,0                   |
| K- 07 10 07 66 | 10 mm x 6,5 mm | 52                 | 4,0                   |
| K- 07 10 07 67 | 10 mm x 6,5 mm | 52                 | 6,0                   |
| K- 07 10 07 68 | 10 mm x 6,5 mm | 52                 | 8,0                   |
| K- 07 10 07 69 | 12 mm x 8 mm   | 65                 | 2,0                   |
| K- 07 10 07 70 | 12 mm x 8 mm   | 65                 | 4,0                   |
| K- 07 10 07 71 | 12 mm x 8 mm   | 65                 | 6,0                   |
| K- 07 10 07 72 | 12 mm x 8 mm   | 65                 | 8,0                   |