

K-EINGANGSPL VENTILINSEL HDM

Input plates for HDM valve terminal

HANSA FLEX

Savybės

| | |
|----------------------------------------|-----------------------------------------------------------------------------------------------------|
| Medžiagos | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Darbinis slėgis | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Valdymo slėgis | 3 - 7 bar |
| Temperatūros diapazonas | -10 °C to +60 °C |
| Srautas | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Valdiklių skaičius | Max. 16 (e.g. 16 spring return valves) |
| Rankinis pagalbinis aktyvinimas | Latching (bistable), Monostable (non-latching) version also available on request |
| Galios sąnaudos | 0.6 W per pilot |
| Apsaugos rūšis | IP 65 |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

Prekė

| Pavadinimas | Funkcija | Jungtis |
|----------------|------------------------------|-----------------------------|
| K- 07 15 22 49 | Standard, internal pilots | Multi-pole |
| K- 07 15 22 48 | External pilots, dual supply | Multi-pole |
| K- 07 15 22 54 | Standard, internal pilots | With integrated Profibus DP |
| K- 07 15 22 53 | External pilots | With integrated Profibus DP |