

K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

HANSA FLEX

Savybės

Eksploatacinė srovė	200 mA
Kabelio srieginė jungtis	M 20 x 1.5
Jungimo funkcija	Positive switching, PNP NO contact, damped or undamped in the end position
Apsaugos rūšis	IP 67, acc. to DIN EN 60529
Temperatūros diapazonas	-20 °C to +70 °C
Korpusas	Polyamide blue or black
Varžtas	Stainless steel 1.4301
Velenas	Polyamide PA6, black
Dangtis	Polycarbonate, transparent
Montavimo tiltelis	PA6 with 30 % glass fibre
Tarpikliai	EPDM and NBR
Sandarinimo medžiaga	NBR



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Prekė

Pavadinimas	Įtampa	Apibrėžtis
K- 07 30 29 06	9 V - 36 V DC	End position feedback, D 2 type with inductive 3-wire sensors