

K-ENDLAGEN-RUECKME KUNST M

End position feedback - plastic microswitch

HANSA FLEX

Savybės

Kabelio srieginė jungtis	M 20 x 1.5
min. atjungiamoji galia	1 mA at 4 V DC
Nominalioji atjungiamoji galia	1 mA to 5 A at 250 V AC
Jungimo funkcija	Changeover, silver-plated contacts
Apsaugos rūšis	IP 67, acc. to DIN EN 60529
Temperatūros diapazonas	-20 °C to +70 °C
Korpusas	Polyamide blue or black
Varžtas	Stainless steel 1.4301
Velenas	Polyamide PA6, black
Dangtis	Polycarbonate, transparent
Montavimo titelis	PA6 with 30 % glass fibre
Tarpikliai	EPDM and NBR
Sandarinimo medžiaga	NBR



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Prekė

Pavadinimas	Apibrėžtis
K- 07 30 29 05	End position feedback, M 2 type with microswitch