
# K-RUNDZYLINDER DOPP O E D MI

Round cylinders, double-acting, with magnet, non-cushioned, »MI« Series





## Savybės

| | |
|---|---|
| **Medžiagos** | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| **Darbinis slėgis** | 1 - 10 bar (double-acting); 2 - 10 bar (single-acting) |
| **Temperatūros diapazonas** | -20 °C to +70 °C |
| **Stūmoklio kotas** | Stainless steel 1.4301 |
| **Konstrukcija** | Type "CA" = ground cover with threaded pin - swivel design<br>Type "CM" = ground cover with threaded pin round - swivel design |
| **Stūmoklis** | Stainless steel 1.4305 (8 to 12 mm); Alu (16 to 40 mm) |
| **Sandarinimo medžiaga** | NBR |
| **Cilindrinis vamzdis** | Stainless steel 1.4301 |

## Nuoroda

Daugiau duomenų pagal užklausimą.

## Aprašas

Circular cylinder in stainless steel in different versions: Series "MI" double-acting, Ø 8 – 25 in accordance with ISO 6432
Series "MI" double-acting, Ø 32 - 40

## Prekė

| Pavadinimas | Stūmoklio Ø | Eiga (mm) | Konstrukcija | Stūmoklio koto Ø (mm) | Stūmoklio koto išoriniai sriegiai |
|---|---|---|---|---|---|
| **K- 07 15 17 90** | 8 mm | 10 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 91** | 8 mm | 15 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 92** | 8 mm | 20 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 93** | 8 mm | 25 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 94** | 8 mm | 30 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 95** | 8 mm | 40 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 96** | 8 mm | 50 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 97** | 8 mm | 60 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 98** | 8 mm | 75 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 17 99** | 8 mm | 80 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 00** | 8 mm | 100 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 01** | 8 mm | 125 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 02** | 8 mm | 150 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 03** | 10 mm | 10 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 04** | 10 mm | 15 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 05** | 10 mm | 20 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 06** | 10 mm | 25 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 07** | 10 mm | 30 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 08** | 10 mm | 40 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 09** | 10 mm | 50 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 10** | 10 mm | 60 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 11** | 10 mm | 75 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 12** | 10 mm | 80 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 13** | 10 mm | 100 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 14** | 10 mm | 125 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 15** | 10 mm | 150 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 16** | 10 mm | 160 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 17** | 10 mm | 175 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 18** | 10 mm | 200 | »CA« type, acc. to ISO 6432 | 4 | M 4 x 0.7 |
| **K- 07 15 18 19** | 12 mm | 10 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 20** | 12 mm | 15 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 21** | 12 mm | 20 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 22** | 12 mm | 25 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 23** | 12 mm | 30 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 24** | 12 mm | 40 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 25** | 12 mm | 50 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |

*Nepaisant kruopštaus patikrinimo, negalime atmesti klaidų tikimybės, todėl už esamus duomenis neatsakome.*

# K-RUNDZYLINDER DOPP O E D MI

Round cylinders, double-acting, with magnet, non-cushioned, »MI« Series

HANSA-FLEX

## Prekė

| Pavadinimas | Stūmoklio Ø | Eiga (mm) | Konstrukcija | Stūmoklio koto Ø (mm) | Stūmoklio koto išoriniai sriegiai |
|---|---|---|---|---|---|
| **K- 07 15 18 26** | 12 mm | 60 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 27** | 12 mm | 75 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 28** | 12 mm | 80 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 29** | 12 mm | 100 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 30** | 12 mm | 125 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 31** | 12 mm | 150 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 32** | 12 mm | 160 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 33** | 12 mm | 175 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 34** | 12 mm | 200 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 35** | 12 mm | 250 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 36** | 16 mm | 10 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 37** | 16 mm | 15 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 38** | 16 mm | 20 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 39** | 16 mm | 25 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 40** | 16 mm | 30 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 41** | 16 mm | 40 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 42** | 16 mm | 50 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 43** | 16 mm | 60 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 44** | 16 mm | 75 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 45** | 16 mm | 80 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 46** | 16 mm | 100 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 47** | 16 mm | 125 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 48** | 16 mm | 150 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 49** | 16 mm | 160 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 50** | 16 mm | 175 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 51** | 16 mm | 200 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 52** | 16 mm | 250 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 53** | 16 mm | 300 | »CA« type, acc. to ISO 6432 | 6 | M 6 x 1 |
| **K- 07 15 18 54** | 20 mm | 10 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 55** | 20 mm | 15 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 56** | 20 mm | 20 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 57** | 20 mm | 25 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 58** | 20 mm | 30 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 59** | 20 mm | 40 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 60** | 20 mm | 50 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 61** | 20 mm | 60 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 62** | 20 mm | 75 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 63** | 20 mm | 80 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 64** | 20 mm | 100 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 65** | 20 mm | 125 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 66** | 20 mm | 150 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 67** | 20 mm | 160 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 68** | 20 mm | 175 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 69** | 20 mm | 200 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 70** | 20 mm | 250 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 71** | 20 mm | 300 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 72** | 20 mm | 350 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 73** | 20 mm | 400 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 74** | 20 mm | 450 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 75** | 20 mm | 500 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 76** | 20 mm | 600 | »CA« type, acc. to ISO 6432 | 8 | M 8 x 1.25 |
| **K- 07 15 18 77** | 25 mm | 10 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 78** | 25 mm | 15 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 79** | 25 mm | 20 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 80** | 25 mm | 25 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 81** | 25 mm | 30 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 82** | 25 mm | 40 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 83** | 25 mm | 50 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 84** | 25 mm | 60 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 85** | 25 mm | 75 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 86** | 25 mm | 80 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 87** | 25 mm | 100 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |

# K-RUNDZYLINDER DOPP O E D MI

Round cylinders, double-acting, with magnet, non-cushioned, »MI« Series

HANSA-FLEX

## Prekė

| Pavadinimas | Stūmoklio Ø | Eiga (mm) | Konstrukcija | Stūmoklio koto Ø (mm) | Stūmoklio koto išoriniai sriegiai |
|---|---|---|---|---|---|
| **K- 07 15 18 88** | 25 mm | 125 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 89** | 25 mm | 150 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 90** | 25 mm | 160 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 91** | 25 mm | 175 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 92** | 25 mm | 200 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 93** | 25 mm | 250 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 94** | 25 mm | 300 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 95** | 25 mm | 350 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 96** | 25 mm | 400 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 97** | 25 mm | 450 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 98** | 25 mm | 500 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 18 99** | 25 mm | 600 | »CA« type, acc. to ISO 6432 | 10 | M 10 x 1.25 |
| **K- 07 15 19 00** | 32 mm | 10 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 01** | 32 mm | 15 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 02** | 32 mm | 20 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 03** | 32 mm | 25 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 04** | 32 mm | 30 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 05** | 32 mm | 40 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 06** | 32 mm | 50 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 07** | 32 mm | 60 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 08** | 32 mm | 75 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 09** | 32 mm | 80 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 10** | 32 mm | 100 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 11** | 32 mm | 125 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 12** | 32 mm | 150 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 13** | 32 mm | 160 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 14** | 32 mm | 175 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 15** | 32 mm | 200 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 16** | 32 mm | 250 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 17** | 32 mm | 300 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 18** | 32 mm | 350 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 19** | 32 mm | 400 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 20** | 32 mm | 450 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 21** | 32 mm | 500 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 22** | 32 mm | 600 | »CM« type | 12 | M 10 x 1.25 |
| **K- 07 15 19 23** | 40 mm | 10 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 24** | 40 mm | 15 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 25** | 40 mm | 20 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 26** | 40 mm | 25 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 27** | 40 mm | 30 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 28** | 40 mm | 40 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 29** | 40 mm | 50 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 30** | 40 mm | 60 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 31** | 40 mm | 75 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 32** | 40 mm | 80 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 33** | 40 mm | 100 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 34** | 40 mm | 125 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 35** | 40 mm | 150 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 36** | 40 mm | 160 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 37** | 40 mm | 175 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 38** | 40 mm | 200 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 39** | 40 mm | 250 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 40** | 40 mm | 300 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 41** | 40 mm | 350 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 42** | 40 mm | 400 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 43** | 40 mm | 450 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 44** | 40 mm | 500 | »CM« type | 16 | M 12 x 1.25 |
| **K- 07 15 19 45** | 40 mm | 600 | »CM« type | 16 | M 12 x 1.25 |

## Priedai

| | |
|---|---|
| **K-FUSSBEFESTIGUNG TYP LB 1** | Foot model, »LB« type |
| **K-FLANSCHBEFESTIGUNG TYP FA3** | Flange model, »FA« type |

*Nepaisant kruopštaus patikrinimo, negalime atmesti klaidų tikimybės, todėl už esamus duomenis neatsakome.*

*Nepaisant kruopštaus patikrinimo, negalime atmesti klaidų tikimybės, todėl už esamus duomenis neatsakome.*