

K-TR POLYURETHAN

Polyurethane hose (PUR)

HANSA FLEX

Savybės

Darbinis slėgis	Max. 10 bar (at +20 °C)
Kietis	52 Shore D±3
Kalibravimas	External
Aplinkos temperatūra	-35 °C to +80 °C
Medžiaga	poliuretanai



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

This externally calibrated plastic hose made of high-quality polyester PUR is extremely flexible with optimal mechanical characteristics and very high pressure resistance across a wide temperature range. It is permanently flexible, boasts very good resilience and can be laid with a narrow bending radius. Its other advantages include good abrasion resistance, very good low-temperature flexibility and very high elongation at break. The hose is also suitable for vacuum applications. It is resistant to many different oils and lubricants (a special resistance test is recommended in specific cases owing to the additives that are blended in by the manufacturers), aliphatic hydrocarbons and gases such as oxygen, ozone, helium, etc.

Prekė

Pavadinimas	Žarnos Ø viduje (mm)	Žarnos Ø išorėje (mm)	Lenkimo spindulys svarbus srautui (mm)	Spalva	Ritinio ilgis (m)
K- 07 10 05 47	2,6	4,0	17	Natural	25
K- 07 10 05 49	3,1	5,0	15	Natural	100
K- 07 10 05 48	3,1	5,0	15	mėlyna	100
K- 07 10 05 51	9,0	12,0	67	Natural	100
K- 07 10 05 52	9,0	12,0	67	juoda	100
K- 07 10 05 54	9,8	14,0	72	Natural	50
K- 07 10 05 53	9,8	14,0	72	mėlyna	50
K- 07 10 05 55	9,8	14,0	72	juoda	50
K- 07 10 05 56	11,0	16,0	88	Natural	50
K- 07 10 05 57	11,0	16,0	88	juoda	50