

K-UEM VA

Hexagonal swivel nuts, stainless steel

HANSA FLEX

Savybės

| | |
|-------------------------|--|
| Slėgio diapazonas | Max. 25 bar |
| rekomenduojamos žarnos | PTFE hose |
| Temperatūros diapazonas | -40 °C to +200 °C (depending on the hose quality and diameter) |
| Medžiaga | nerūdijantis plienas 1.4404 |
| Tarpiklis | Pure metal |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Prekė

| Pavadinimas | Sriegis | žarnai | SW (rakto dydis) |
|----------------|----------|--------------|------------------|
| K- 07 40 30 53 | M 10 x 1 | 6 mm / 4 mm | 12 mm |
| K- 07 40 30 54 | M 12 x 1 | 8 mm / 6 mm | 14 mm |
| K- 07 40 30 55 | M 14 x 1 | 10 mm / 8 mm | 16 mm |