

K-SVKM NW 7,6 AG ST-MS VZ

Quick disconnect couplings DN 7.6, galvanised steel / brass, male

HANSA FLEX

Savybės

| | |
|-----------------------|---|
| Darbinis slėgis | Max. 16 bar |
| Oro srautas | 2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Medžiagos temperatūra | -20 °C to +100 °C |
| Korpusas | Steel |
| Spyruoklė | Stainless-steel |
| Išstumiama įvorė | Hardened and nickel-plated steel |
| Sandarinimo medžiaga | NBR |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The "stream line" type has an integrated hose stem.

Prekė

| Pavadinimas | Jungtis | Ilgis (mm) | SW (mm) |
|----------------|------------|------------|---------|
| K- 07 35 07 77 | R 1/4 male | 63,0 | 20 |
| K- 07 35 07 78 | R 3/8 male | 61,0 | 20 |
| K- 07 35 07 79 | R 1/2 male | 56,0 | 22 |

Papildomos dalys

| | |
|-------------------------------|---|
| K-NIPPEL KUPPL NW7 AG VZ PTFE | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal |
| K-NIPPEL KUPPL NW7 IG VZ 1 | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female |
| K-NIPPEL KUPPL STREAM LINE | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line« |
| K-TUE 7,2 7,8 ST VZ 2 | Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel |