# K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

## Savybės

| | |
|---|---|
| **Medžiagos** | Filtered, unlubricated compressed air |
| **Darbinis slėgis** | 2.5 - 8 bar |
| **Temperatūros diapazonas** | -10 °C to +60 °C |
| **Jungtis** | Push-in fitting for pipe 4 mm |
| **Aktyvinimo įtaisas** | Pneumatic |
| **6 bar oro srauto kiekis** | 85 Nl/min |
| **maks. įėjimo signalo laiko poslinkis** | 0,4 s |



## Nuoroda

Daugiau duomenų pagal užklausimą.

## Aprašas

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter.Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

## Prekė

| Pavadinimas | Apibrėžtis | Jungtis |
|---|---|---|
| **K- 07 15 26 09** | Two-hand safety valve without housing | Push-in fitting for 4 mm pipe |
| **K- 07 15 26 10** | mounting element | - |