


# K-BKR LANG IG AG

Ball valves, long-threaded type, female/male thread

**HANSA FLEX**

## Savybės

<b>Taikymo sritis</b>	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
<b>Darbinis slėgis</b>	Max. 40 bar
<b>Darbinė temperatūra</b>	-15 °C to +90 °C
<b>Sriegių aprašas</b>	Thread acc. to ISO 7-1
<b>Korpusas</b>	Nickel-plated brass
<b>Svirtis</b>	Aluminium, painted black
<b>Kūgis</b>	Chrome-plated brass
<b>Rutulio sandariklis</b>	PTFE
<b>Velenėlio sandarinimas</b>	NBR / EPDM



## Nuoroda

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Daugiau duomenų pagal užklausimą.

## užsakymo nuorodos

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Papildoma informacija

The pressure values refer to a maximum operating temperature of 40 °C. Lower maximum pressure apply at higher temperatures. See data sheet.

## Prekė

Pavadinimas	DN	Sriegis	A (mm)	B (mm)	L (mm)
K- 07 30 21 37	8	Rp/R 1/4	85,0	42,0	52,0
K- 07 30 21 38	10	Rp/R 3/8	85,0	42,0	54,0
K- 07 30 21 39	15	Rp/R 1/2	85,0	46,0	67,0
K- 07 30 21 40	20	Rp/R 3/4	105,0	53,0	78,0
K- 07 30 21 41	25	Rp/R 1	105,0	57,0	89,0
K- 07 30 21 42	32	Rp/R 1 1/4	130,0	70,0	103,0
K- 07 30 21 43	40	Rp/R 1 1/2	130,0	76,0	113,0
K- 07 30 21 44	50	Rp/R 2	165,0	92,0	136,0