

K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

HANSA FLEX

Savybės

| | |
|--|---------------------------------------|
| Darbinis slėgis | 0 - 35 bar |
| Oro srautas | 2.100 l/min (at $\Delta p = 0.5$ bar) |
| Medžiagos temperatūra | -20 °C to +40 °C |
| Sriegio dalis | Nickel-plated brass |
| Vožtuvo korpusas | Steel, QPQ treated |
| Atblokavimo įvorė | Extremely robust, ergonomic plastic |
| Vožtuvas, lizdas | Brass |
| Medžiagos | Only for clean compressed air |
| Tarpikliai | NBR |
| Spyruoklė, spyruoklinis atraminis žiedas, rutuliai | stain less steel |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Prekė

| Pavadinimas | Jungtis | Ilgis (mm) | SW (mm) |
|----------------|------------|---------------|------------|
| K- 07 35 08 47 | G 1/4 male | 65,0 | 19 |
| K- 07 35 08 48 | G 3/8 male | 65,0 | 19 |
| K- 07 35 08 49 | G 1/2 male | 59,0 | 22 |

Papildomos dalys

| | |
|-------------------------------|--|
| K-NIPP KUPPL NW7 SCHL MS NI K | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring |
| K-NIPPEL KUPPL NW7 AG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male |
| K-NIPPEL KUPPL NW7 IG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female |
| K-NIPPEL KUPPL NW7 SCHL MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose |
| K-TUE 7,2 7,8 MS NI | Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass |