

K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

HANSA FLEX

Savybės

Darbinis slėgis	0 - 35 bar
Oro srautas	2.100 l/min (at $\Delta p = 0.5$ bar)
Medžiagos temperatūra	-20 °C to +40 °C
Sriegio dalis	Nickel-plated brass
Vožtuvo korpusas	Steel, QPQ treated
Atblokavimo įvorė	Extremely robust, ergonomic plastic
Vožtuvas, lizdas	Brass
Medžiagos	Only for clean compressed air
Tarpikliai	NBR
Spyruoklė, spyruoklinis atraminis žiedas, rutuliai	stain less steel



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Prekė

Pavadinimas	Jungtis	Ilgis (mm)	SW (mm)
K- 07 35 08 50	G 1/4 female	59,0	19
K- 07 35 08 51	G 3/8 female	59,0	19
K- 07 35 08 52	G 1/2 female	62,0	24

Papildomos dalys

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass