

K-WV 5/2 EINS ELEKTRO

5/2-way spool valves, single solenoid

HANSA FLEX

Savybės

| | |
|-------------------------|---|
| Funkcija | 5/2-way |
| Darbinis slėgis | 2.5 - 10 bar; Max. vacuum 10 bar (external pilot air) |
| min. darbinis slėgis | 2,5 bar |
| Temperatūros diapazonas | -10 °C to +60 °C |
| 6 bar ir 10 bar srautas | 1500 NI/min (G 1/4), 4600 NI/min (G 1/2) |
| Elektros jungtis | Coupler plug PG 9 - form B |
| Apsaugos rūšis | IP 65 (DIN 46244) |
| Korpusas | Anodised aluminium, blue |
| Stūmoklio stūmiklis | Stainless steel |
| Sandarinio medžiaga | NBR |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality. The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems. Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

Prekė

| Pavadinimas | Jungtis | Įtampa | DN | Jungimo schemos numeris | Valdymas |
|----------------|---------|-----------------|----|-------------------------|----------|
| K- 07 15 02 21 | G 1/4 | 24 V DC | 8 | 35 | |
| K- 07 15 02 22 | G 1/2" | 24 V DC | 15 | 35 | |
| K- 07 15 02 23 | G 1/4 | 230 V AC, 50 Hz | 8 | 35 | |
| K- 07 15 02 24 | G 1/2" | 230 V AC, 50 Hz | 15 | 35 | |