


K-VENTILSCHEIBE HDM 8

Valve discs for HDM valve terminal with 8 mm port

HANSA FLEX

Savybės

| | |
|--|---|
| Medžiagos | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Darbinis slėgis | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Valdymo slėgis | 3 - 7 bar |
| Temperatūros diapazonas | -10 °C to +60 °C |
| Srautas | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Valdiklių skaičius | Max. 16 (e.g. 16 spring return valves) |
| Rankinis pagalbinis aktyvinimas | Latching (bistable), Monostable (non-latching) version also available on request |
| Galios sąnaudos | 0.6 W per pilot |
| Apsaugos rūšis | IP 65 |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

Prekė

| Pavadinimas | Funkcija |
|----------------|--|
| K- 07 15 20 69 | 2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted |
| K- 07 15 20 72 | 2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised |
| K- 07 15 20 63 | 3/2-way, NC, monostable and 3/2-way, NO, monostable |
| K- 07 15 20 71 | 5/2-way, monostable |
| K- 07 15 20 68 | 5/2-way, monostable (uses only one pin, two signals assigned) |
| K- 07 15 20 70 | 5/2-way, bistable (pulse valve) |
| K- 07 15 20 65 | 5/3-way, mid-position closed |