

K-ENDPLATTEN V

End plate for HDM valve terminal

Savybės

Medžiagos	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Darbinis slėgis	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Valdymo slėgis	3 - 7 bar
Temperatūros diapazonas	-10 °C to +60 °C
Srautas	200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)
Valdiklių skaičius	Max. 16 (e.g. 16 spring return valves)
Funkcija	Blind (terminates the system)
Rankinis pagalbinis aktyvinimas	Latching (bistable), Monostable (non-latching) version also available on request
Galios sąnaudos	0.6 W per pilot
Apsaugos rūšis	IP 65



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

Prekė

Pavadinimas	Funkcija
K- 07 15 22 50	Blind (terminates the system)