# K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continous thread

## Savybės

| | |
|---|---|
| **Darbinis slėgis** | Max. 50 bar |
| **Jungties sriegiai** | acc. ISO 7-1 |
| **Medžiaga** | black steel ST 37-2 |



## Nuoroda

Daugiau duomenų pagal užklausimą.

## Aprašas

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses.Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. they are also protected against rust.They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

## Prekė

| Pavadinimas | Sriegis | Ilgis (mm) |
|---|---|---|
| **K- 07 40 35 30** | R 1/4 | 25,0 |
| **K- 07 40 35 33** | R 3/8 | 26,0 |
| **K- 07 40 35 29** | R 1/2 | 34,0 |
| **K- 07 40 35 32** | R 3/4 | 36,0 |
| **K- 07 40 35 26** | R 1 | 43,0 |
| **K- 07 40 35 28** | R 1 1/4 | 48,0 |
| **K- 07 40 35 27** | R 1 1/2 | 48,0 |
| **K- 07 40 35 31** | R 2 | 56,0 |
| **K- 07 40 50 36** | R 2 1/2 | 65,0 |
| **K- 07 40 50 37** | R 3 | 71,0 |