


K-WTEH 3-TLG PC SCHU VARIOBLOC

Service units, 3-piece with polycarbonate bowl and bowl guard

HANSA FLEX

Savybės

| | |
|------------------------------------|---|
| lėjimo slėgis | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| Medžiagos temperatūra | max. 50 °C |
| Aplinkos temperatūra | Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl) |
| Porų plotis filtro elemento | 40 µm |
| Sandaravimo medžiaga | NBR |
| Spyruoklės gaubtas | POM |
| Korpusas | Die-cast zinc |
| Membrana | NBR |
| Lašėjimo antgalis | PA |
| Drain valve | Manual |
| Srauto reikšmės matavimas | At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

užsakymo nuorodos

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges (0.5 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

Papildoma informacija

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges.

Prekė

| Pavadinimas | Sriegis | Reguliavimo diapazonas | Srautas (L/min) | A (mm) | B | C (mm) |
|----------------|---------|------------------------|-----------------|--------|----------|--------|
| K- 07 25 22 86 | G 1/4 | 0.5 - 10 bar | 1500 | 144,0 | 201,0 mm | 68,0 |
| K- 07 25 22 85 | G 3/8 | 0.5 - 10 bar | 1800 | 144,0 | 201,0 mm | 68,0 |
| K- 07 25 22 84 | G 1/2 | 0.5 - 10 bar | 3400 | 210,0 | 247,0 mm | 98,0 |
| K- 07 25 22 83 | G 3/4 | 0.5 - 10 bar | 5000 | 210,0 | 247,0 mm | 98,0 |
| K- 07 25 22 82 | G 1 | 0.5 - 10 bar | 5000 | 264,0 | 247,0 mm | 98,0 |