K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

Savybės

Darbinis slėgis	maks. 10 bar
Oro srautas	1.800 l/min (at 6 bar and Δp = 1 bar)
Medžiagos temperatūra	-20 °C to +150 °C
Korpusas	Stainless steel 1.4404
Sriegiai	Stainless steel 1.4404
Vidinės dalys	Stainless steel 1.4404
Rankenėlė, vožtuvas	Stainless steel 1.4404
Sandarinimo medžiaga	FKM



Nuoroda

Not suitable for hitting / pulsating tools.
Daugiau duomenų pagal užklausimą.

Aprašas

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Papildoma informacija

Not suitable for hitting / pulsating tools.

Prekė

Pavadinimas	Jungtis	Ilgis (mm)	SW (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24