

# K-LKM S NW7,4 DREH SCHL TUE VA

Safety couplings DN 7.4, stainless steel 1.4404, with hose stem, swivel type

**HANSA FLEX**

## Savybės

<b>Darbinis slėgis</b>	maks. 10 bar
<b>Oro srautas</b>	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Medžiagos temperatūra</b>	-20 °C to +150 °C
<b>Korpusas</b>	Stainless steel 1.4404
<b>Sriegiai</b>	Stainless steel 1.4404
<b>Vidinės dalys</b>	Stainless steel 1.4404
<b>Rankenėlė, vožtuvas</b>	Stainless steel 1.4404
<b>Sandarinio medžiaga</b>	FKM



## Nuoroda

Not suitable for hitting / pulsating tools.  
Daugiau duomenų pagal užklausimą.

## Aprašas

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Papildoma informacija

Not suitable for hitting / pulsating tools.

## Prekė

Pavadinimas	Jungtis	Ilgis (mm)	SW (mm)
K- 07 35 12 83	Stem, I.D. 6	88,5	21
K- 07 35 12 85	Stem, I.D. 9	88,5	21
K- 07 35 12 86	Stem, I.D. 13	88,5	21