

K-LKM S NW7,2 AG

Safety couplings DN 7.2, male

HANSA FLEX

Savybės

Darbinis slėgis	0 - 35 bar, maximum static working pressure (non-pulsating)
Oro srautas	1.100 l/min (at $\Delta p = 0.5$ bar)
Medžiagos temperatūra	-30 °C to +100 °C
Korpusas, mova, vožtuvo korpusas	Nickel-plated brass
Spyruoklė, rutuliai	Stainless-steel
Sandarinimo medžiaga	NBR



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

Prekė

Pavadinimas	Jungtis	Ilgis (mm)	SW (mm)
K- 07 35 02 92	G 1/4 male	44,0	22
K- 07 35 02 93	G 3/8 male	44,0	22
K- 07 35 02 94	G 1/2 male	47,0	24

Papildomos dalys

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,