

K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media,
nonlinearity 0.2%

HANSA FLEX

Savybės

Tipas	S-11
Įtampa	DC 10 (14) ... 30 V
Elektros jungtis	With right-angle connector acc. to DIN EN 175301-803 A
Apsaugos rūšis	IP 65 acc. to EN 60529
Išėjimo signalas	4 to 20 mA, 2-wire
Netiesiškumas	0.2% of span
Medžiagos temperatūra	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
Aplinkos temperatūra	-20 °C to +80 °C
Dalys, su kuriomis liečiasi matavimo medžiaga	CrNi steel 1.4571
Korpusas	CrNi steel 1.4571



Aprašas

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Papildoma informacija

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Prekė

Pavadinimas	Matavimo sritis	Sriegis
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Atsarginės dalys

K-ZUBEH DRUCKMESSUMFOR Accessoires for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%