


K-L-STECKVER ISK DREH AG OR

Banjo elbows with inner hex, swivel type, parallel male thread with O-ring

HANSA FLEX

Savybės

Darbinis slėgis	Max. 15 bar, coarse vacuum
Taikymo sritys	Air, vacuum
rekomenduojamos žarnos	PU or PA (nylon)
Medžiagos	Compressed air and all gases or liquids that are compatible with the materials
Temperatūros diapazonas	-20 °C to +80 °C
Sandarinio paviršius	Parallel version: O-ring in housing
Medžiaga	Plastic, Nickel plated brass
Prispaudimo žiedas	Plastic



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Prekė

Pavadinimas	Sriegis	žarnos išoriniam Ø	Vidinis šešiabriaunis (mm)	L1 (mm)	L2 (mm)	SW (rakto dydis)
K- 07 40 05 91	G 1/8	4 mm	4,0	22,5	28,5	14 mm
K- 07 40 05 92	G 1/8	6 mm	4,0	21,5	28,5	14 mm
K- 07 40 05 93	G 1/8	8 mm	4,0	24,5	28,5	14 mm
K- 07 40 05 89	G 1/4	6 mm	6,0	23,5	36,5	17 mm
K- 07 40 05 90	G 1/4	8 mm	6,0	26,5	36,5	17 mm
K- 07 40 05 87	G 1/4	10 mm	6,0	29,9	36,5	17 mm
K- 07 40 05 88	G 1/4	12 mm	6,0	30,8	36,5	17 mm
K- 07 40 05 96	G 3/8	8 mm	8,0	28,5	39,2	20 mm
K- 07 40 05 94	G 3/8	10 mm	8,0	31,9	39,2	20 mm
K- 07 40 05 95	G 3/8	12 mm	8,0	32,8	39,2	20 mm
K- 07 40 42 65	G 1/2	12 mm	8,0	35,4	42,7	24 mm