

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Savybės

Vidinis sluoksnis Soft-PVC, black

Įdėklas poliesterio apypinas

Išorinis sluoksnis Soft-PVC, blue

Temperatūra -20 °C to +60 °C

Ritinio ilgis 50 m



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Prekė

| Pavadinimas | Žarnos Ø viduje (mm) | Žarnos Ø išorėje (mm) | Max. working pressure resistance at 23°C (bar) | Min. lenkimo spindulys (mm) |
|----------------|-------------------------|--------------------------|---|--------------------------------|
| K- 07 10 10 33 | 6,3 | 11,0 | 15 | 23 |
| K- 07 10 10 34 | 8,0 | 13,0 | 15 | 28 |
| K- 07 10 10 35 | 9,0 | 14,5 | 15 | 32 |
| K- 07 10 10 36 | 10,0 | 15,5 | 15 | 35 |
| K- 07 10 10 37 | 12,7 | 19,0 | 15 | 45 |
| K- 07 10 10 38 | 16,0 | 23,0 | 15 | 56 |
| K- 07 10 10 39 | 19,0 | 26,5 | 15 | 67 |
| K- 07 10 10 40 | 25,0 | 33,5 | 15 | 88 |