


K-DLV MULTI-LINK SCHNELLVER

Compressed air distributor, type »Multi-Link« quick disconnect safety couplings DN 7.6

HANSA FLEX

Savybės

| | |
|-------------------------|-------------------------------------|
| Darbinis slėgis | Max. 16 bar |
| Temperatūros diapazonas | -20 °C to +80 °C |
| Medžiaga | Galvanised steel / brass |
| Jungtis | G 1/2 female |
| Medžiagos | Compressed air, non-corrosive gases |
| Sandarinimo medžiaga | NBR |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units:
- DN 7.6 quick disconnect safety couplings.

Prekė

| Pavadinimas | Jungtis | Išėmimo vienetai |
|----------------|-------------------------|------------------|
| K- 07 35 13 70 | Safety couplings DN 7.6 | 1 |
| K- 07 35 13 73 | Safety couplings DN 7.6 | 2 |
| K- 07 35 13 76 | Safety couplings DN 7.6 | 3 |
| K- 07 35 13 79 | Safety couplings DN 7.6 | 4 |
| K- 07 35 13 82 | Safety couplings DN 7.6 | 5 |