

K-DURCHGANGSVERTEILERDOSE

Through porting box with through-hole thread, PN 15

HANSA FLEX

Savybės

| | |
|----------------------------|--------------------------------|
| Darbinis slėgis | Max. 15 bar |
| Tvirtinimo sukimo momentas | 4 Nm |
| MS sriegių sukimo momentas | 12 Nm |
| Temperatūros diapazonas | -10 °C to +50 °C |
| Korpusas | Glass fibre-reinforced plastic |
| Sriegiai | Brass |



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Prekė

| Pavadinimas | Įėjimo sriegis | Pereigos sriegiai | Jungties sriegis |
|----------------|----------------|-------------------|------------------|
| K- 07 40 48 04 | G 1/2" | G 1/2 | 1 x G 1/2 |
| K- 07 40 48 05 | G 1/2" | G 1/2 | 2 x G 1/2 |
| K- 07 40 48 06 | G 1/2" | G 1/2 | 3 x G 1/2 |
| K- 07 40 48 07 | G 3/4" | G 3/4 | 1 x G 1/2 |
| K- 07 40 48 08 | G 3/4" | G 3/4 | 2 x G 1/2 |
| K- 07 40 48 09 | G 3/4" | G 3/4 | 3 x G 1/2 |