

K-LECKAGESUCHGERAET

Leakage finder

HANSA FLEX

Savybės

Darbinis dažnis	40 kHz ± 2 kHz
Jungtis	4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable
Lazeris	Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW
Energijos tiekimas	Internal NiMH rechargeable battery
Veikimo trukmė	Approx. 6 hours without laser / 4 hours with laser
Krovimo trukmė	Approx. 1.5 hours
Naudojimo temperatūra	0 °C to +40 °C
Sandėliavimo temperatūra	-10 °C to +50 °C



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems.
The advantages of the LS 100: Simple and quick measurement, even from distances of several metres. Measurements can be taken on running systems, without affecting their operation. The device is quickly amortised by the high cost savings.

Prekė

Pavadinimas	Aprašymas
K- 07 25 19 53	Leak detection device, including accessories in a practical carrying case

Priedai

K-ALU-TELESKOPSTANGE	Aluminium-telescopic pole
-----------------------------	---------------------------