


K-T-STUECKE 134 IG IG AG

Tees 134, female/female/male

HANSA FLEX

Savybės

Paviršius	Hot dip galvanised
Temperatūros diapazonas	-20 °C to +300 °C (at 20 bar)
Jungties sriegiai	acc. ISO 7-1
Medžiaga	Black malleable iron B350-10, design symbol A
Leidimas	DIN DVGW



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Papildoma informacija

Further types and dimensions on request.

Prekė

Pavadinimas	1 sriegiai	2 sriegiai	3 sriegiai
K- 07 40 52 14	Rp 1/2	R 1/2	Rp 1/2
K- 07 40 52 16	Rp 3/4	R 3/4	Rp 3/4
K- 07 40 52 11	Rp 1	R 1	Rp 1
K- 07 40 52 13	Rp 1 1/4	R 1 1/4	Rp 1 1/4
K- 07 40 52 12	Rp 1 1/2	R 1 1/2	Rp 1 1/2
K- 07 40 52 15	Rp 2	R 2	Rp 2