K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Savybės

Panaudojimas	Air, gases, oils, greases, fuels, organic and inorganic substances
Darbinė temperatūra	-40 °C to +100 °C
Prijungimo būdas	connection nipples and coupling NW 7,2



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Prekė

Pavadinimas	Žarnos Ø viduje (mm)	Žarnos Ø išorėje (mm)	Spiralės Ø išorėje (mm)	Vijos	Max. working pressure resistance at 23°C (bar)	maks. darbinis ilgis (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Priedai

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector