K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass

Savybės

Prijungimo būdas	connection nipples and coupling NW 7,2
Darbinė temperatūra	-40 °C to +74 °C



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Prekė

Pavadinimas	Žarnos Ø viduje (mm)	Žarnos Ø išorėje (mm)	Išorinės vijos Ø (mm)	Max. working pressure resistance at 23°C (bar)	maks. darbinis ilgis (m)
K- 07 10 12 72	5,0	8,0	40	10	3,0
K- 07 10 12 74	5,0	8,0	40	10	6,0
K- 07 10 12 76	5,0	8,0	40	10	7,5
K- 07 10 12 81	6,3	9,5	60	10	3,0
K- 07 10 12 83	6,3	9,5	60	10	6,0
K- 07 10 12 85	6,3	9,5	60	10	7,5
K- 07 10 12 79	6,3	9,5	60	10	10,0
K- 07 10 12 90	8,0	12,0	80	9	3,0
K- 07 10 12 92	8,0	12,0	80	9	6,0
K- 07 10 12 94	8,0	12,0	80	9	7,5
K- 07 10 12 88	8,0	12,0	80	9	10,0

Priedai

K-DREHBARE VERSCHRAUBUNG	Swivel adapters