


# K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

**HANSA FLEX**

## Savybės

maks. eksploatacinis slėgis	0,7 MPa
min. eksploatacinis slėgis	0.10 MPa
Konstrukcija	rack and pinion
Medžiagos temperatūra	0 °C to +60 °C
Aplinkos temperatūra	0 °C to +60 °C
Pasukimo kampas	0 to 190°
Medžiagos	suslėgtas oras
A serija	MSQ
Daugiau duomenų	narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible



## Prekė

Pavadinimas	Stūmoklio Ø (mm)	Pneumatinė jungtis	Gaminio dydis	Slopinimas	Svoris kas m (kg)
K- 07 55 01 13	6	M 3	1	without, with adjustment bolt	0,075
K- 07 55 01 18	8	M 5	2	without, with adjustment bolt	0,105
K- 07 55 01 21	10	M 5	3	elastic, with adjustment bolt	0,150
K- 07 55 01 26	12	M 5	7	elastic, with adjustment bolt	0,250
K- 07 55 01 11	15	M 5	10	elastic, with adjustment bolt	0,530
K- 07 55 01 16	18	M 5	20	elastic, with adjustment bolt	0,990
K- 07 55 01 19	21	G 1/8	30	elastic, with adjustment bolt	1,290
K- 07 55 01 22	25	G 1/8	50	elastic, with adjustment bolt	2,080
K- 07 55 01 24	28	G 1/8	70	elastic, with adjustment bolt	2,880
K- 07 55 01 09	32	G 1/8	100	elastic, with adjustment bolt	4,090
K- 07 55 01 14	40	G 1/8	200	elastic, with adjustment bolt	7,580
K- 07 55 01 12	15	M 5	10	elastic, with integrated shock absorber	0,540
K- 07 55 01 17	18	M 5	20	elastic, with integrated shock absorber	0,990
K- 07 55 01 20	21	G 1/8	30	elastic, with integrated shock absorber	1,290
K- 07 55 01 23	25	G 1/8	50	elastic, with integrated shock absorber	2,100
K- 07 55 01 25	28	G 1/8	70	elastic, with integrated shock absorber	2,880
K- 07 55 01 10	32	G 1/8	100	elastic, with integrated shock absorber	4,100
K- 07 55 01 15	40	G 1/8	200	elastic, with integrated shock absorber	7,650