

K-SENSOREN CS1 RD OHNE STECKER

Sensors »CS1« type, cable without plug

HANSA FLEX



Prekė

Pavadinimas	Stūmoklio Ø	Konstrukcija
K- 07 15 22 91	8 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 22 92	10 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 22 93	12 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 22 94	16 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 22 95	20 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 22 96	25 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 22 97	32 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 22 98	40 mm	Hall sensor, 3-wire, with 3 m cable length, NO, NPN
K- 07 15 23 07	8 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 23 08	10 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 23 09	12 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 23 10	16 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 23 11	20 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 23 12	25 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 23 13	32 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 23 14	40 mm	Hall sensor, 3-wire, with 3 m cable length, NO, PNP
K- 07 15 22 75	8 mm	Reed sensor, 2-wire, with 3 m cable length, NO
K- 07 15 22 76	10 mm	Reed sensor, 2-wire, with 3 m cable length, NO
K- 07 15 22 77	12 mm	Reed sensor, 2-wire, with 3 m cable length, NO
K- 07 15 22 78	16 mm	Reed sensor, 2-wire, with 3 m cable length, NO
K- 07 15 22 79	20 mm	Reed sensor, 2-wire, with 3 m cable length, NO
K- 07 15 22 80	25 mm	Reed sensor, 2-wire, with 3 m cable length, NO
K- 07 15 22 81	32 mm	Reed sensor, 2-wire, with 3 m cable length, NO
K- 07 15 22 82	40 mm	Reed sensor, 2-wire, with 3 m cable length, NO

priedai šiems gaminiams

K-RUNDZYLINDER DOPP O E D MI	Round cylinders, double-acting, with magnet, non-cushioned, »MI« Series
K-RUNDZYLINDER EINF DL O D MSI	Round cylinders, single-acting (pressureless in the retracted position), with magnet, non-cushioned, »MSI« Series