

LKM HR ST DK

Įkišamos movos įvorė (oras) su apsauga

HANSA FLEX

Savybės

Konstrukcija	greito uždarymo movos įvorė
1 jungtis	cilindrinis BSP išorinis sriegis
2 jungtis	
Darbinis slėgis	maks. 12 bar
Oro srautas	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Medžiagos temperatūra	-20 °C to +70 °C
Korpusas	Aluminium, anodised
Sriegiai	Nickel-plated brass
Vidinės dalys	Stainless steel
Rankenėlė, vožtuvas	Hardened, galvanised steel
Sandarinio medžiaga	NBR



Nuoroda

Not suitable for hitting / pulsating tools.

Daugiau duomenų pagal užklausimą.

Aprašas

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Prekė

Pavadinimas	Jungties sriegis	Jungtis	Ilgis (mm)	SW (mm)
LKM 06 HR ST DK	G 1/4" -19	G 1/4 male	70,5	21
LKM 10 HR ST DK	G 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	G 1/2" -14	G 1/2 male	72,5	25