

# LKM MM ST DK

Įkišamos movos įvorė (oras) su apsauga

**HANSA FLEX**

## Savybės

Konstrukcija	greito uždarymo movos įvorė
1 jungtis	žarnos jungtis
2 jungtis	
Darbinis slėgis	maks. 12 bar
Oro srautas	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Medžiagos temperatūra	-20 °C to +70 °C
Korpusas	Aluminium, anodised
Sriegiai	Nickel-plated brass
Vidinės dalys	Stainless steel
Rankenėlė, vožtuvas	Hardened, galvanised steel
Sandarinio medžiaga	NBR



## Nuoroda

Not suitable for hitting / pulsating tools.  
Daugiau duomenų pagal užklausimą.

## Aprašas

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Prekė

Pavadinimas	žarnos ID (mm)	Jungtis	Ilgis (mm)	SW (mm)
LKM 06 MM ST DK	6	Stem, I.D. 6	88,5	21
LKM 09 MM ST DK	9	Stem, I.D. 9	88,5	21
LKM 13 MM ST DK	13	Stem, I.D. 13	88,5	21