

# 2 OK VA

## 2 cilpu apskava

### Īpašības

**Izmantošana** Šūteņu stiprinājumi zema spiediena zonā

**Materiāls** Centrējošais gredzens no alumīnija ar Viton gredzenblīvi



### Izstrādājums

| Apzīmējums      | Iespēlēšanas diapazons (mm) | Lentes platums (mm) |
|-----------------|-----------------------------|---------------------|
| 2 OK 3-5 VA     | 3,4 - 5,0                   | 5,0                 |
| 2 OK 3.1-4.1 VA | 3,1 - 4,1                   | 3,5                 |
| 2 OK 3.5-4.5 VA | 3,5 - 4,5                   | 3,5                 |
| 2 OK 5-7 VA     | 5,0 - 7,0                   | 6,0                 |
| 2 OK 7-9 VA     | 7,0 - 9,0                   | 6,0                 |
| 2 OK 8-11 VA    | 8,0 - 11,0                  | 7,0                 |
| 2 OK 9-11 VA    | 9,0 - 11,0                  | 6,5                 |
| 2 OK 11-13 VA   | 11,0 - 13,0                 | 6,5                 |
| 2 OK 13-15 VA   | 13,0 - 15,0                 | 7,0                 |
| 2 OK 15-17 VA   | 15,0 - 17,0                 | 7,5                 |
| 2 OK 15-18 VA   | 15,0 - 18,0                 | 7,5                 |
| 2 OK 17-20 VA   | 17,0 - 20,0                 | 7,5                 |
| 2 OK 18-21 VA   | 18,0 - 21,0                 | 8,0                 |
| 2 OK 19-22 VA   | 18,1 - 22,0                 | 9,0                 |
| 2 OK 20-23 VA   | 20,0 - 23,0                 | 8,0                 |
| 2 OK 22-25 VA   | 22,0 - 25,0                 | 8,5                 |
| 2 OK 23-27 VA   | 23,0 - 27,0                 | 8,5                 |
| 2 OK 25-28 VA   | 25,0 - 28,0                 | 9,0                 |
| 2 OK 27-31 VA   | 26,3 - 31,0                 | 10,0                |
| 2 OK 28-31 VA   | 28,0 - 31,0                 | 9,0                 |
| 2 OK 31-34 VA   | 31,0 - 34,0                 | 9,5                 |
| 2 OK 34-37 VA   | 34,0 - 37,0                 | 9,5                 |
| 2 OK 37-40 VA   | 37,0 - 40,0                 | 10,0                |
| 2 OK 40-43 VA   | 40,0 - 43,0                 | 10,0                |
| 2 OK 43-46 VA   | 43,0 - 46,0                 | 10,0                |

### Izstrādājumu varianti

2 OK 2 cilpu apskava, galvaniskais pārklājums

2 OK VC 2 cilpu apskava, spīdīgs hromēts-cinkots