

## Īpašības

Modelis	Gliemežvītnes skavas
Papildinājums modelim	Sešstūra skrūves galviņa ar mīnusu
Materiāls	Nerūsējošais tērauds 1.4436



## Izstrādājums

Apzīmējums	Iespēšanas diapazons (mm)	Lentes platums (mm)
ESK 08-14 W5	8 - 14	9,0
ESK 11-17 W5	11 - 17	9,0
ESK 13-20 W5	13 - 20	9,0
ESK 15-24 W5	15 - 24	9,0
ESK 19-28 W5	19 - 28	12,0
ESK 22-32 W5	22 - 32	12,0
ESK 26-38 W5	26 - 38	12,0
ESK 32-44 W5	32 - 44	12,0
ESK 38-50 W5	38 - 50	12,0
ESK 44-56 W5	44 - 56	12,0
ESK 50-65 W5	50 - 65	12,0
ESK 58-75 W5	58 - 75	12,0
ESK 68-85 W5	68 - 85	12,0
ESK 77-95 W5	77 - 95	12,0
ESK 87-112 W5	87 - 112	12,0
ESK 104-138 W5	104 - 138	12,0
ESK 130-165 W5	130 - 165	12,0
ESK 150-180 W5	150 - 180	12,0
ESK 175-205 W5	175 - 205	12,0
ESK 200-231 W5	200 - 231	12,0
ESK 226-256 W5	226 - 256	12,0
ESK 251-282 W5	251 - 282	12,0
ESK 277-307 W5	277 - 307	12,0

## Izstrādājumu varianti

ESK

## Piederumi

SCHRAUBENDR Lokans skrūvgriezis