

# CR (2,5 - 3,5 mm)

Vara blīvgredzens, biezums 2,5 - 3,5 mm

**HANSA FLEX**

## Īpašības

|                  |              |
|------------------|--------------|
| Modelis          | Blīvgredzens |
| Temperatūra min. | -50 °C       |
| Temperatūra max. | 300 °C       |
| Materiāls        | Varš         |



## Izstrādājums

| Apzīmējums      | d1<br>(mm) | d2<br>(mm) | S<br>(mm) |
|-----------------|------------|------------|-----------|
| CR 6.2-17.5-2.5 | 6,20       | 17,50      | 2,50      |
| CR 11-24-2.5    | 11,00      | 24,00      | 2,50      |
| CR 52-60-2.5    | 52,00      | 60,00      | 2,50      |
| CR 60-68-2.5    | 60,00      | 68,00      | 2,50      |
| CR 64-72-2.5    | 64,00      | 72,00      | 2,50      |
| CR 65-74-2.5    | 65,00      | 74,00      | 2,50      |
| CR 75-84-2.5    | 75,00      | 84,00      | 2,50      |
| CR 90-100-2.5   | 90,00      | 100,00     | 2,50      |
| CR 21-27-3      | 21,00      | 27,00      | 3,00      |
| CR 35-42-3.5    | 35,00      | 42,00      | 3,50      |