

SAE O-RING V

SAE apaļā veida gredzens FKM

HANSA FLEX

Īpašības

Temperatūra min. -15 °C

Temperatūra max. 200 °C

Materiāls FKM SH 90 (Viton)



Izstrādājums

| Apzīmējums | Atloka izmērs | Ø d1 (mm) | S (mm) |
|--------------------|---------------|--------------|-----------|
| SAE O-RING 1/2 V | 1/2" | 18,64 | 3,53 |
| SAE O-RING 3/4 V | 3/4" | 24,99 | 3,53 |
| SAE O-RING 1 V | 1" | 32,92 | 3,53 |
| SAE O-RING 1 1/4 V | 1.1/4" | 37,69 | 3,53 |
| SAE O-RING 1 1/2 V | 1.1/2" | 47,22 | 3,53 |
| SAE O-RING 2 V | 2" | 56,74 | 3,53 |
| SAE O-RING 2 1/2 V | 2.1/2" | 69,44 | 3,53 |
| SAE O-RING 3 V | 3" | 85,32 | 3,53 |
| SAE O-RING 3 1/2 V | 3.1/2" | 98,02 | 3,53 |
| SAE O-RING 4 V | 4" | 110,72 | 3,53 |

Izstrādājumu varianti

SAE O-RING SAE apaļa šķērsriezuma gredzens, NBR SH 90