

# K-DIFFERENZDRUCKMANO Z

Differential pressure gauges with parallel male connector

**HANSA FLEX**

## Īpašības

<b>Tips</b>	711.12
<b>Modelis</b>	Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems
<b>Izmantošana</b>	to measure differential pressures or two different pressures For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
<b>Kvalitātes klase</b>	1,6
<b>Vielas temperatūra</b>	maks. +60 °C
<b>Vides temperatūra</b>	no -20 °C līdz +60 °C
<b>Korpuss, gredzens</b>	Steel, black
<b>Mērelementa un rādītāja materiāls</b>	Vara sakausējums
<b>Skatstikls</b>	Flat instrument glass



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Izstrādājums

Apzīmējums	Mērīšanas diapazons	Ø (mm)	Savienojums
K- 07 20 00 55	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 56	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 57	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 58	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 59	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 60	0 - 10.0 bar	100,0	G 1/2"