

K-DIFFERENZDRUCKMANO Z

Differential pressure gauges with parallel male connector

HANSA FLEX

Īpašības

Tips	711.12
Modelis	Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems
Izmantošana	to measure differential pressures or two different pressures For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kvalitātes klase	1,6
Vielas temperatūra	maks. +60 °C
Vides temperatūra	no -20 °C līdz +60 °C
Korpuss, gredzens	Steel, black
Mērelementa un rādītāja materiāls	Vara sakausējums
Skatstikls	Flat instrument glass



Norāde

Citi dati pieejami pēc pieprasījuma.

Izstrādājums

Apzīmējums	Mērīšanas diapazons	Ø (mm)	Savienojums
K- 07 20 00 55	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 56	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 57	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 58	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 59	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 60	0 - 10.0 bar	100,0	G 1/2"