

K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

HANSA FLEX

Īpašības

Tips	422.12 (robust), 432.50 (chemical)
Modelis	Diaphragm pressure gauge in robust design or for chemical applications
Izmantošana	at chemical applications in aggressive environments for gaseous or liquid media,
Kvalitātes klase	1,6
Vielas temperatūra	max. +100 °C
Vides temperatūra	no -20 °C līdz +60 °C
Ø mērīšanas atloks	100 mm
Korpuss, gredzens	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
Mērelements	CrNi steel
Skatstikls	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
Rādītāja mehānisms	Copper alloy (robust type), CrNi steel (type for chemical applications)



Norāde

Citi dati pieejami pēc pieprasījuma.

Izstrādājums

Apzīmējums	Mērīšanas diapazons	Ø (mm)	Savienojums
K- 07 20 10 99	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 00	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 11 01	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 11 02	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 11 03	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 11 04	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 11 05	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 11 06	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 11 07	0 - 25.0 bar	100,0	G 1/2"