

# K-PRMM CHEMIE U

Diaphragm pressure gauges for chemical applications, connection radial on bottom

**HANSA FLEX**

## Īpašības

<b>Tips</b>	422.12 (robust), 432.50 (chemical)
<b>Modelis</b>	Diaphragm pressure gauge in robust design or for chemical applications
<b>Izmantošana</b>	at chemical applications in aggressive environments for gaseous or liquid media,
<b>Kvalitātes klase</b>	1,6
<b>Vielas temperatūra</b>	max. +100 °C
<b>Vides temperatūra</b>	no -20 °C līdz +60 °C
<b>Ø mērīšanas atloks</b>	100 mm
<b>Korpuss, gredzens</b>	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
<b>Mērelements</b>	CrNi steel
<b>Skatstikls</b>	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
<b>Rādītāja mehānisms</b>	Copper alloy (robust type), CrNi steel (type for chemical applications)



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Izstrādājums

Apzīmējums	Mērīšanas diapazons	Ø (mm)	Savienojums
K- 07 20 10 25	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 10 26	0 - 10.0 bar	100,0	G 1/2"